

UNITED STATES DISTRICT COURT
EASTERN DISTRICT OF NEW YORK

CORNELIUS SAVAGE,

Plaintiff,

Case No. _____

-v-

COMPLAINT

FULTON ALE HOUSE, LLC and
1446 FULTON LLC,

Defendants.
_____X

Plaintiff, Cornelius Savage, by his undersigned counsel, hereby files this Complaint and
sues, Fulton Ale House, LLC and 1446 Fulton LLC, for injunctive relief pursuant to the
Americans with Disabilities Act, 42 U.S.C. § 12181, et seq., (hereinafter the “A.D.A”) and the
ADA’s Accessibility Guidelines, 28 C.F.R. Part 36 (hereinafter the “ADAAG”).

JURISDICTION

1. This Court has original jurisdiction over the action pursuant to 28 U.S.C., §§1331
and 1343 for Plaintiff’s claims arising under 42 U.S.C. § 12181. et seq., based upon
Defendant’s violations of Title III of the ADA (see also, 28 U.S.C. §§ 2201 and 2202).

2. Plaintiff, Cornelius Savage, currently resides in Queens, New York, and is *sui
juris*. He is a qualified individual with disabilities under the ADA law. Mr. Savage is a double
leg amputee. As a result Mr. Savage is bound to ambulate in a wheelchair. He has visited the
property, which forms the basis of this lawsuit and plan to return to the property to avail himself
of the goods and services offered to the public at the property, and to determine whether the
property has been made ADA compliant. His access to the facility and/or full and equal
enjoyment of the goods, services, facilities, privileges, advantages, and/or accommodations
offered therein was denied and/or limited because of these disabilities, and will be denied and/or

limited in the future unless and until Defendants are compelled to remove the physical barriers to access and ADA violations which exist at the facility, including but not limited, to those set forth in the Complaint.

3. Defendant, 1446 Fulton LLC, is a business who transacts business in the State of New York and within this judicial district. Defendant is the owner/lessor, of the real property, which is the subject of this action located on or about at 1446 Fulton St, Brooklyn, NY 11216 (hereinafter the “Facility”).

4. Defendant, Fulton Ale House, LLC, is a domestic corporation and transacts business in the State of New York and within this judicial district. Defendant is the lessee of the premises located at 1446 Fulton St, Brooklyn, NY 11216, and the owner/operator of a restaurant located at the premises.

5. The Defendants’ Facility is a public accommodation and service establishment, and although required by law to do so, it is not in compliance with the ADA and ADAAG.

6. In this instance, Plaintiff visited the Facility and encountered barriers to access at the Facility, engaged barriers, suffered legal harm and injury, and will continue to suffer legal harm and injury as a result of the illegal barriers to access as set forth herein.

7. Plaintiff has suffered and continues to suffer direct and indirect injury as a result of the ADA violations that exist at the Facility.

8. All events giving rise to this lawsuit occurred in the State of New York. Venue is proper in this Court as the premises are located in the Eastern District.

FACTUAL ALLEGATIONS AND CLAIM

9. Plaintiff has attempted to access the facility, but could not do so without severe hardship, because of his disabilities, and the physical barriers to access and ADA violations that

exist at the Facility, which restrict and/or limit his access to the goods and services offered at the Facility. The ADA violations are more specifically set forth in this Complaint.

10. Plaintiff intends to visit the Facility again in the near future in order to utilize all of the goods and services offered therein but will be unable to do so because of the physical barriers to access, dangerous conditions and ADA violations that exist at the facility that restrict and/or limit his access to the facility, including those barriers conditions and ADA violations more specifically set forth in this Complaint.

11. Defendants have discriminated against Plaintiff and others with disabilities by denying access to, and full and equal enjoyment of the goods and services of the facility, as prohibited by 42 U.S.C., § 12182, *et.seq.*, and by failing to remove architectural barriers as required by 42 U.S.C., § 12182(b)(2)(A)(iv), and will continue to discriminate against Plaintiff and others with disabilities unless and until Defendants are compelled to remove all physical barriers that exist at the facility, including those specifically set forth herein, and make the facility accessible to and usable by persons with disabilities, including Plaintiff.

12. Defendants have discriminated against Plaintiff by failing to comply with the above requirements. A specific, although not exclusive, list of unlawful physical barriers, dangerous conditions and ADA violations, which preclude and/or limit Plaintiff's ability to access the Facility and full and equal enjoyment of the goods, services offered at the Facility include:

- I. INACCESSIBLE ENTRANCE. ACCESSIBLE ROUTE TO ESTABLISHMENT NOT PROVIDED AS REQUIRED. ACCESSIBLE MEANS OF EGRESS NOT PROVIDED AS REQUIRED. EXISTING STEP AT ENTRANCE ACTS AS A BARRIER TO ACCESSIBILITY. REQUIRED RAMP NOT PROVIDED FOR STEP AT ENTRANCE.
 - a. ADAAG 206 Accessible Routes ADAAG 206.1 General. Accessible routes shall be provided in accordance with 206 and shall comply with Chapter 4. ADAAG 206.2 Where Required. Accessible routes shall be

provided where required by 206.2. ADAAG 206.2.1 Site Arrival Points. At least one accessible route shall be provided within the site from accessible parking spaces and accessible passenger loading zones; public streets and sidewalks; and public transportation stops to the accessible building or facility entrance they serve. ADAAG 206.4 Entrances. Entrances shall be provided in accordance with 206.4. Entrance doors, doorways, and gates shall comply with 404 and shall be on an accessible route complying with 402. ADAAG 206.4.1 Public Entrances. In addition to entrances required by 206.4.2 through 206.4.9, at least 60 percent of all public entrances shall comply with 404. ADAAG 207 Accessible Means of Egress ADAAG 207.1 General. Means of egress shall comply with section 1003.2.13 of the International Building Code (2000 edition and 2001 Supplement) or section 1007 of the International Building Code (2003 edition) (incorporated by reference, "Referenced Standards" in Chapter 1). ADAAG 303.4 Ramps. Changes in level greater than ½ inch high shall be ramped, and shall comply with 405 or 406.

- II. **REQUIRED MINIMUM MANEUVERING CLEARANCE NOT PROVIDED AT ENTRANCE DOOR. NON-COMPLIANT CHANGE IN FLOOR LEVEL WITHIN REQUIRED MANEUVERING CLEARANCE AT ENTRANCE DOOR.**
 - a. ADAAG 404.2.4 Maneuvering Clearances. Minimum maneuvering clearances at doors and gates shall comply with 404.2.4. Maneuvering clearances shall extend the full width of the doorway and the required latch side or hinge side clearance. ADAAG 404.2.4.4 Floor or Ground Surface. Floor or ground surface within required maneuvering clearances shall comply with 302. Changes in level are not permitted.
- III. **INACCESSIBLE DINING TABLES LOCATED AT INTERIOR DINING AREA. NON-COMPLIANT HEIGHT OF INTERIOR DINING TABLES EXCEEDS MAXIMUM HEIGHT ALLOWANCE. REQUIRED MINIMUM KNEE AND TOE CLEARANCE NOT PROVIDED AT INTERIOR DINING TABLES. MINIMUM PERCENTAGE OF EXISTING INTERIOR DINING TABLES REQUIRED TO BE ACCESSIBLE NOT PROVIDED.**
 - a. ADAAG 226 Dining Surfaces and Work Surfaces ADAAG 226.1 General. Where dining surfaces are provided for the consumption of food or drink, at least 5 percent of the seating spaces and standing spaces at the dining surfaces shall comply with 902.
 - b. ADAAG 902.2 Clear Floor or Ground Space. A clear floor space complying with 305 positioned for a forward approach shall be provided. Knee and toe clearance complying with 306 shall be provided. ADAAG 902.3 Height. The tops of dining surfaces and work surfaces shall be 28 inches (710 mm) minimum and 34 inches (865 mm) maximum above the finish floor or ground. ADAAG 306.2 Toe Clearance. ADAAG 306.2.3 Minimum Required Depth. Where toe clearance is required at an element as part of a clear floor space,

the toe clearance shall extend 17 inches (430 mm) minimum under the element. ADAAG 306.2.5 Width. Toe clearance shall be 30 inches (760 mm) wide minimum. ADAAG 306.3 Knee Clearance. ADAAG 306.3.3 Minimum Required Depth. Where knee clearance is required under an element as part of a clear floor space, the knee clearance shall be 11 inches deep minimum at 9 inches above the ground, and 8 inches deep minimum at 27 inches (685 mm) above the finish floor or ground. ADAAG 306.3.5 Width. Knee clearance shall be 30 inches (760 mm) wide minimum.

IV. INACCESSIBLE BAR.
NON-COMPLIANT HEIGHT OF BAR EXCEEDS MAXIMUM
HEIGHT ALLOWANCE.
REQUIRED MINIMUM KNEE AND TOE CLEARANCE NOT
PROVIDED AT BAR. PORTION OF BAR REQUIRED TO BE
ACCESSIBLE NOT PROVIDED.

- a. ADAAG 226 Dining Surfaces and Work Surfaces ADAAG 226.1 General. Where dining surfaces are provided for the consumption of food or drink, at least 5 percent of the seating spaces and standing spaces at the dining surfaces shall comply with 902. ADAAG 902 Dining Surfaces and Work Surfaces ADAAG 902.1 General. Dining surfaces and work surfaces shall comply with 902.2 and 902.3. Advisory 902.1 General. Dining surfaces include, but are not limited to, bars, tables, lunch counters, and booths. ADAAG 902.2 Clear Floor or Ground Space. A clear floor space complying with 305 positioned for a forward approach shall be provided. Knee and toe clearance complying with 306 shall be provided. ADAAG 902.3 Height. The tops of dining surfaces and work surfaces shall be 28 inches (710 mm) minimum and 34 inches (865 mm) maximum above the finish floor or ground. ADAAG 306.2 Toe Clearance. ADAAG 306.2.3 Minimum Required Depth. Where toe clearance is required at an element as part of a clear floor space, the toe clearance shall extend 17 inches (430 mm) minimum under the element. ADAAG 306.2.5 Width. Toe clearance shall be 30 inches (760 mm) wide minimum. ADAAG 306.3 Knee Clearance. ADAAG 306.3.3 Minimum Required Depth. Where knee clearance is required under an element as part of a clear floor space, the knee clearance shall be 11 inches deep minimum at 9 inches above the ground, and 8 inches deep minimum at 27 inches (685 mm) above the finish floor or ground. ADAAG 306.3.5 Width. Knee clearance shall be 30 inches (760 mm) wide minimum.

V. INACCESSIBLE EXTERIOR DINING AREA. INACCESSIBLE
DINING TABLES AT EXTERIOR DINING AREA. INACCESSIBLE
TRAVEL PATH TO EXTERIOR DINING TABLES. NON-
COMPLIANT FLOOR SURFACE AT EXTERIOR DINING AREA
ACTS AS A BARRIER TO ACCESSIBILITY.

- a. ADAAG 403.2 Floor or Ground Surface. Floor or ground surfaces shall comply with 302. ADAAG 302 Floor or Ground Surfaces

- ADAAG 302.1 General. Floor and ground surfaces shall be stable, firm, and slip resistant and shall comply with 302.
- VI. NON-COMPLIANT SEATING BENCHES LOCATED AT EXTERIOR DINING AREA. REQUIRED BACK SUPPORT NOT PROVIDED AT SEATING BENCHES LOCATED AT EXTERIOR DINING AREA. SEATING BENCH LOCATED IN THE SECOND OF FOUR DRESSING ROOMS IS NOT AFFIXED TO A WALL.
- a. ADAAG 903 Benches ADAAG 903.4 Back Support. The bench shall provide for back support or shall be affixed to a wall. Back support shall be 42 inches (1065 mm) long minimum and shall extend from a point 2 inches (51 mm) maximum above the seat surface to a point 18 inches (455 mm) minimum above the seat surface. Back support shall be 2½ inches (64 mm) maximum from the rear edge of the seat measured horizontal.
- VII. COMPLIANT SIGNAGE IDENTIFYING THE RESTROOM NOT PROVIDED AS REQUIRED.
- a. ADAAG 216 Signs ADAAG 216.1 General. Signs shall be provided in accordance with 216 and shall comply with 703.
- b. ADAAG 216.2 Designations. Interior and exterior signs identifying permanent rooms and spaces shall comply with 703.1, 703.2, and 703.5. Where pictograms are provided as designations of permanent interior rooms and spaces, the pictograms shall comply with 703.6 and shall have text descriptors complying with 703.2 and 703.5. Advisory 216.2 Designations. Section 216.2 applies to signs that provide designations, labels, or names for interior rooms or spaces where the sign is not likely to change over time. Examples include interior signs labeling restrooms, room and floor numbers or letters, and room names. Tactile text descriptors are required for pictograms that are provided to label or identify a permanent room or space. Pictograms that provide information about a room or space, such as “no smoking,” occupant logos, and the International Symbol of Accessibility, are not required to have text descriptors. ADAAG 703.1 General. Signs shall comply with 703. Where both visual and tactile characters are required, either one sign with both visual and tactile characters, or two separate signs, one with visual, and one with tactile characters, shall be provided. ADAAG 703.4.1 Height Above Finish Floor or Ground. Tactile characters on signs shall be located 48 inches (1220 mm) minimum above the finish floor or ground surface, measured from the baseline of the lowest tactile character and 60 inches (1525 mm) maximum above the finish floor or ground surface, measured from the baseline of the highest tactile character. ADAAG 703.4.2 Location. Where a tactile sign is provided at a door, the sign shall be located alongside the door at the latch side. Where a tactile sign is provided at double doors with one active leaf, the sign shall be located on the inactive leaf. Where a tactile sign is provided at double doors with two active leaves, the sign shall be located to the right of the right hand

door. Where there is no wall space at the latch side of a single door or at the right side of double doors, signs shall be located on the nearest adjacent wall. Signs containing tactile characters shall be located so that a clear floor space of 18 inches (455 mm) minimum by 18 inches (455 mm) minimum, centered on the tactile characters, is provided beyond the arc of any door swing between the closed position and 45 degree open position.

- VIII. INACCESSIBLE LAVATORY IN RESTROOM. REQUIRED MINIMUM KNEE AND TOE CLEARANCE NOT PROVIDED AT LAVATORY IN RESTROOM.
 - a. ADAAG 606 Lavatories and Sinks ADAAG 606.2 Clear Floor Space. A clear floor space complying with 305, positioned for a forward approach, and knee and toe clearance complying with 306 shall be provided. ADAAG 306.2 Toe Clearance. ADAAG 306.2.3 Minimum Required Depth. Where toe clearance is required at an element as part of a clear floor space, the toe clearance shall extend 17 inches (430 mm) minimum under the element. ADAAG 306.2.5 Width. Toe clearance shall be 30 inches (760 mm) wide minimum. ADAAG 306.3 Knee Clearance. ADAAG 306.3.3 Minimum Required Depth. Where knee clearance is required under an element as part of a clear floor space, the knee clearance shall be 11 inches deep minimum at 9 inches above the ground, and 8 inches deep minimum at 27 inches (685 mm) above the finish floor or ground. ADAAG 306.3.5 Width. Knee clearance shall be 30 inches (760 mm) wide minimum.
- IX. NON-COMPLIANT HEIGHT OF LAVATORY IN RESTROOM EXCEEDS MAXIMUM HEIGHT ALLOWANCE.
 - a. ADAAG 606.3 Height. Lavatories and sinks shall be installed with the front of the higher of the rim or counter surface 34 inches (865 mm) maximum above the finish floor or ground.
- X. INACCESSIBLE MIRROR IN RESTROOM. NON COMPLIANT MOUNTED HEIGHT OF MIRROR IN RESTROOM EXCEEDS MAXIMUM HEIGHT ALLOWANCE.
 - a. ADAAG 603.3 Mirrors. Mirrors located above lavatories or countertops shall be installed with the bottom edge of the reflecting surface 40 inches (1015 mm) maximum above the finish floor or ground. Mirrors not located above lavatories or countertops shall be installed with the bottom edge of the reflecting surface 35 inches (890 mm) maximum above the finish floor or ground.
- XI. INACCESSIBLE WATER CLOSET IN RESTROOM. NON-COMPLIANT DISTANCE OF WATER CLOSET FROM SIDE WALL IN RESTROOM.
 - a. ADAAG 604.2 Location. The water closet shall be positioned with a wall or partition to the rear and to one side. The centerline of the water closet shall be 16 inches minimum to 18 inches maximum from the side wall or partition.

- XII. INACCESSIBLE TOILET PAPER DISPENSER. NON-COMPLIANT MOUNTED HEIGHT OF TOILET PAPER DISPENSER EXCEEDS MAXIMUM HEIGHT ALLOWANCE.
 - a. ADAAG 604.9.6 Dispensers. Toilet paper dispensers shall comply with 309.4 and shall be 7 inches minimum and 9 inches maximum in front of the water closet measured to the centerline of the Dispenser. The outlet of the dispenser shall be 14 inches minimum and 19 inches maximum above the finish floor. There shall be a clearance of 1½ inches minimum below the grab bar. Dispensers shall not be of a type that controls delivery or that does not allow continuous paper flow.
- XIII. NON-COMPLIANT DOOR KNOB AT RESTROOM DOOR REQUIRES TWISTING OF THE WRIST.
 - a. ADAAG 404.2.7 Door and Gate Hardware. Handles, pulls, latches, locks, and other operable parts on doors and gates shall comply with 309.4 ADAAG 309.4 Operation. Operable parts shall be operable with one hand and shall not require tight grasping, pinching, or twisting of the wrist. The force required to activate operable parts shall be 5 pounds maximum.
- XIV. NON-COMPLIANT DOOR LOCK AT RESTROOM DOOR REQUIRES TWISTING OF THE WRIST.
 - a. ADAAG 404.2.7 Door and Gate Hardware. Handles, pulls, latches, locks, and other operable parts on doors and gates shall comply with 309.4 ADAAG 309.4 Operation. Operable parts shall be operable with one hand and shall not require tight grasping, pinching, or twisting of the wrist. The force required to activate operable parts shall be 5 pounds maximum.

13. The above listing is not to be considered all-inclusive of the barriers, which exist at the Facility. Plaintiff requires an inspection of the facility, in order to determine all of the ADA violations.

14. The removal of the physical barriers, dangerous conditions and ADA violations set forth herein is readily achievable and can be accomplished and carried out without much difficulty or expense. 42 U.S.C. § 12182(B)(2)(A)(iv); 42 U.S.C. § 12181(9); 28 C.F.R. § 36.304.

15. Plaintiff is without adequate remedy at law and is suffering irreparable harm, and reasonably anticipates that he will continue to suffer irreparable harm unless and until

Defendants are required to remove the physical barriers, dangerous conditions and ADA violations that exist at the facility, including those set forth herein.

16. The Plaintiff has been obligated to retain undersigned counsel for the filing and prosecution of this action. The Plaintiff is entitled to have his reasonable attorney's fees, costs and expenses paid by the Defendants, pursuant to 42 U.S.C., §§ 12205 and 12217.

17. Pursuant to 42 U.S.C. §12188(a), this Court is provided with authority to grant injunctive relief to Plaintiff, including an order to alter the subject facility to make it readily accessible to and useable by individuals with disabilities to the extent required by the ADA, and closing the subject facility until the requisite modifications are completed.

WHEREFORE, Plaintiff respectfully requests that the Court issue a permanent injunction enjoining Defendants from continuing is discriminatory practices, ordering Defendants to remove the physical barriers to access and alter the subject facility to make it readily accessible to and useable by individuals with disabilities to the extent required by the ADA, closing the subject facility until the barriers are removed and requisite alterations are completed, and awarding Plaintiff his reasonable attorney's fees, expert fees, costs and litigation expenses incurred in this action.

Respectfully submitted,

s/Maria Costanza Barducci
Maria Costanza Barducci, Esq.
BARDUCCI LAW FIRM
Attorneys for Plaintiff
5 West 19th Street, 10th Floor
New York, New York 10011
Bar No.: 5070487
Telephone: 212-433-2554
Email: mc@barduccilaw.com